

Übersicht Lochbleche

Rundlochung Versetzt	Wst. 1.4301 1000x2000 mm (kf)	Einseitig geschliffen	Beidseitig geschliffen	Wst. 1.4301 1250x2500 mm (mf)	Wst. 1.4301 1500x3000 mm (gf)	Wst. 14571
Rv 1,1 - 2,0	0,8					
Rv 1,5 - 2,5	0,5 1,0					
Rv 2,0 - 3,5	1,0 1,5			1,0 1,5		1,0 1,5 kf
Rv 3,0 - 5,0	0,5 0,8 1,0 1,5 2,0			1,0 1,5	1,0+1,5	1,0 1,5 2,0 kf
Rv 3,0 - 4,0	0,8					
Rv 4,0 - 6,0	1,0 1,5 2,0			1,0		
Rv 5,0 - 7,0	0,5 1,0					
Rv 5,0 - 8,0	0,8 1,0 1,5 2,0 3,0	1,5 kf + mf	1,5+2 kf + mf	0,8 1,0 1,5 2,0	1,0 1,5 2,0	1,0 1,5 2,0 3,0 kf 1,0+1,5 mf 1,5 gf
Rv 6,0 - 8,0	1,0					
Rv 6,0 - 9,0	1,5					
Rv 8,0 - 10,0	1,5					
Rv 8,0 - 11,0	1,0 1,5 2,0					
Rv 8,0 - 12,0	1,0 1,5 2,0 3,0		1,5 kf	1,0 1,5 2,0	1,5	1,5 2,0 kf
Rv 10,0 - 13,0	1,0					
Rv 10,0 - 15,0	1,0 1,5 2,0 3,0	1,5 kf+ mf	1,5 kf+ mf + gf, 2 kf	1,0 1,5 2,0	1,5 2,0	1,5 2,0 kf
Rv 15,0 - 21,0	1,5		1,5 kf			
Rv 20,0 - 28	2,0		1,5 kf + mf	2,0	2,0	
Rv 30,0 - 40,0			1,5 kf			

Rundlochung geradreihig	Wst. 1.4301 1000x2000 mm (kf)	Einseitig geschliffen	Beidseitig geschliffen	Wst. 1.4301 1250x2500 mm (mf)	Wst. 1.4301 1500x3000 mm (gf)	Wst. 14571
Rg 4,5 – 15,0	1,5	1,50 kf	1,5 kf + mf	1,5		
Rg 8,0 – 17,32	1,5					
Rg 10,0 – 15,0		1,5 kf + mf	1,5 kf			
Rg 10,0 – 20,78			1,5 kf + mf			
Rg 10,0 – 25,98	1,5		1,5 kf + mf	1,5		
Rg 12 – 27,72			1,5 kf			
Rg 15,0 – 36,38			1,5 kf			
Rg 20,0 – 48,5	1,5		1,5 kf + 1,50x1000x 2500 mm			
Quadratlochung geradreihig	Wst. 1.4301 1000x2000 mm (kf)	Einseitig geschliffen	Beidseitig geschliffen	Wst. 1.4301 1250x2500 mm (mf)	Wst. 1.4301 1500x3000 mm (gf)	Wst. 14571
Qg 5,0 – 8,0	1,0 1,5 2,0	1,5 kf	1,5 kf	1,0 1,5		
Qg 5,0 – 16,0	1,5	1,5 kf + mf	1,5 kf + mf			
Qg 8,0 – 10,0	1,0 1,5			1,5		
Qg 8,0 – 12,0	1,0 1,5 2,0		1,50 kf	1,5	1,5	
Qg 8,0 – 24,0	1,5		1,5 kf			
Qg 10,0 – 12,0	1,0 1,5			1,5	1,5	
Qg 10,0 – 14,0	1,0 1,5 2,0					
Qg 10,0 – 15,0	1,0 1,5 2,0	1,5 kf + mf	1,5 kf + gf	1,0 1,5 2,0	1,5 + 2,0	1,5 2,0 kf
Qg 10,0 – 30,0	1,5	1,0 kf 1,5 kf +mf + gf	1,5 kf +mf + gf 1,5x1000x 2500	1,5		
Qg 15,0 – 40,0	1,5		1,5 kf + mf + gf			
Qg 15,0 – 60,0			1,5 kf + mf			
Qg 20,0 – 50,0	1,5	1,5 kf	1,5 kf + mf + gf	1,5		

Qg 25,0 – 70,0			1,5 kf			
Quadratlochung versetzt	Wst. 1.4301 1000x2000 mm (kf)	Einseitig geschliffen	Beidseitig geschliffen	Wst. 1.4301 1250x2500 mm (mf)	Wst. 1.4301 1500x3000 mm (gf)	Wst. 14571
Qv 10 – 30		1,5 Kf				
Elyptischelochung versetzt	Wst. 1.4301 1000x2000 mm (kf)	Einseitig geschliffen	Beidseitig geschliffen	Wst. 1.4301 1250x2500 mm (mf)	Wst. 1.4301 1500x3000 mm (gf)	Wst. 14571
EVL 15 – 30/25 - 80			1,5 kf			
EVH 30-70/100-100	1,5		1,5 kf + mf			
EVH 8-32/50-50			1,5 kf + mf			
Rechtecklochung	Wst. 1.4301 1000x2000 mm (kf)	Einseitig geschliffen	Beidseitig geschliffen	Wst. 1.4301 1250x2500 mm (mf)	Wst. 1.4301 1500x3000 mm (gf)	Wst. 14571
RE 5-15/35-35			1,5 kf			
Langloch						
LVL 5 – 20	1,5					

Einfassprofile für Lochbleche gibt es in 10+18+27 mm Rund, 10x12, 12x18, 20x30 mm Rechteck und 20 mm Vkt.

Übersicht Steckgitter in Wst. 4301

Maschenlänge	Maschenbreite	Stegbreite	Stegdicke	Größe	Form	kg/Tfl.	
16	8	1,5	1,0	1000x2000	Raute	6,0	
20	10	2,0	1,0	1000x2000	Raute	6,0	
20	15	1,7	1,5	1000x2000	Quadrat	5,2	
30	17	2,5	1,5	1000x2000	Raute	7,4	
43	13	2,5	1,5	1000x2000	Raute	9,2	
62	23	3,0	2,0	1000x2000	Raute	9,2	